

HALOSTAR STARLITE

35 W 12 V GY6.35



Product benefits

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires (to IEC 60598-1)
- Axial filament for optimum directional light
- · Special pins for corrosion protection
- UV filter
- Contains no mercury, can be thrown away with normal household waste

Product features

Average life: 4,000 h100 % dimmable

• Base: G4, GY6.35

• Color rendering index R_a : 100









Technical data

Electrical data

Rated wattage	35 W
Nominal wattage	35 W
Rated number of switching cycles	1000000 1)
Rated power factor λ	1.00

¹⁾ At 1 s on / 1 s off


Light technical data


Nominal luminous flux	580 lm
Rated luminous flux	580 lm
Rated color temperature	2900 K
Rated color rendering index Ra	100
Rated starting time	0.0 s
Rated warm-up time (60 %)	0 s
Lumen main.fact.at end of nom.life time	0.80

Dimensions & weight

Length	44.0 mm
Overall length	44.0 mm
Diameter	12.0 mm
Light center length (LCL)	30.0 mm
Outer bulb	T12







Product line drawing with letters

Base

Colors & materials

Rated lamp mercury content	0.0 mg
Mercury-free	Yes

Lifespan

Nominal lamp life time	4000 h
Rated lamp life time	4000 h

Additional product data

Base (standard designation)	GY6.35
Filament setting	Axial

Capabilities

Product datasheet



Capabilities

Burning position	hs30
------------------	------

Country specific categorizations

ILCOS	HSGST/C/UB-35-12-GY6,35-12/30



Logistical Data

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4050300017426	Folding carton box 1	25 mm x 20 mm x 70 mm	5.00 g	0.04 dm ³
4050300942179	Shipping carton box 40	121 mm x 107 mm x 144 mm	208.00 g	1.86 dm ³

Product datasheet



Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.