

CAUTION

1. **SAVE THIS INSTRUCTIONS-** This manual contains important safety and operating instructions for the EP6012A battery charger.
Please read the caution of batteries or devices you want to charge firstly!
2. When charging, batteries can emit explosive gases, therefore it is essential to prevent flames and sparks. The charger is designed for charging lead-acid batteries from 7 to 80 Ah. Do not use for any other purpose.
3. Always provide good ventilation when charging.
4. Use of an attachment not recommended or sold by Everpower may result in a risk of fire, electric shock or serious injury to persons.
5. To reduce risk of damage to electric plug and cord, pull by the plug rather than by the cord when disconnecting charger.
6. An extension cord should not be used unless absolutely necessary. Use of an improper extension cord could result in a risk of fire and electric shock. If extension cord must be used, make sure that: a) Pins on plug of extension cord are the same number, size and shape as those of plug on charger; b) Extension cord is properly wired and in good electrical condition; and c) Wire size is large enough for ac ampere rating as specified in "technical data".
7. Do not operate charger with a damaged cord or plug-return the charger to the place where purchased.
8. Never operate the charger if it has received a sharp blow, been dropped or otherwise damaged in any way; take it to a qualified serviceman.
9. Do not disassemble the charger; take it to a qualified serviceman when service or repair is required. Incorrect reassembly may result in a risk of electrical shock or fire.
10. To reduce risk of electric shock, unplug charger from AC outlet before attempting any maintenance or cleaning. Turning off controls will not reduce the risk.

EVERPOWER
艾威博尔

EP6012A
12V Lead-Acid Battery Charger

User's Manual



May, 2011 3rd Version

Everpower Electronics Co.,Ltd

Brief Introduction

EP6012A is a main member of digital-chargers from Everpower Electronics Co.,Ltd It represents today 's new technology for lead-acid type battery charging. EP6012A programmed four auto stages (Ud-Im-Uo-Up) charging process. It is designed for all kinds of 12V 7~80Ah lead-acid battery, such as SLA, AGM and Gel battery. Stage "Ud" desulfurating the battery through 18V pulse, When the battery recovered, stage "Im" will give bulk current charging(3.3A or 2.0A). Then, "Uo" stage is followed, the output voltage is limited on 14.7V; When the battery is nearly full, stage"Up" will turn on duty. At this stage, the battery is charged completely and the charger give some pulse to maintenance the battery.


Further,EP60 can display the charging process, indicate the battery capacity from 25% to 100% timely. This is helpful for user.

For more safety, EP60 will inter protection mode when the battery polarity reversed or the output connectors shorted.

Specification for EP6012A[S]

Input Voltage	100-240VAC, 50-60Hz
Input Current	1.1A
Back current drain	1.3mA
Charge voltage	Rating 12V, Bulk limited voltage : 14.7V
Ripple current	Current-ripple:<= 0.13A rms
Bulk charge current	3.3A for EP6012A, 2.0A for EP6012AS
Operate Temperature	-20℃~50℃,
Cooling	Natural convection. Do not cover the charger.
Charge principle	Auto 4 stages: Ud-I-Uo-Up
Battery type	All types of 12V lead-acid batteries.(SLA, Gel, AGM....)
Battery capacity	7-80Ah for EP6012A, 4~40Ah for EP6012AS
Size	120X67X41mm
Enclosure	IP54 (Dust protected, Water splashing resistance)
Weight	270g

Display Panel



How to use:

1. Connect the AC cord to the socket, The "power" lamp will light on solid. indication light will indicate a battery which is connected to reverse polarity.
2. Connect positive charger clip (red) to positive battery terminal, the black clip to negative. (You can use other dc plugs to connect battery), the "25%~100%" lamps will light on flowing. If the battery polarity reversed or output shorted, all lamps will flashing, please check the setup.
3. Depend on the charged capacity, 25%~100% lamps will lights up solid sequence, the battery is fully charged. Then you can power off the charger and disconnect the battery or you can charge a new battery if you need.

The table shows the duration of the Bulk stepup to about 80% state of charge..

Battery type (Ah)	EP6012A (hours)	EP6012AS (hours)
12	3	5
22	7	10
45	14	20
75	22	Not recommend