



No.2290C

CMOS LSI
LC7582,7582E,7582W

LCD Driver

Overview

The LC7582,7582E,7582W is a general-purpose LCD driver designed for use in electronic tuning frequency display or microcomputer-controlled system applications.


Features

- 53 segments (max.) output (Static display)
- Drive system: 1/1duty (53 segments), 1/2duty (104 segments)
- Data input: 3 serial input pins
- 2 pins for 5-level AD converter (Level meter use, etc.)
- 2 display (DSP) pins for direct display
- INH pin for blanking out display


Absolute Maximum Ratings at $T_a=25^{\circ}\text{C}$, $V_{SS}=0\text{V}$

			unit
Maximum Supply Voltage	$V_{DD\max}$	V_{DD}	-0.3 to +7.0 V
Input Voltage	V_{LCD} $V_{IN(1)}$	V_{LCD} CE, CLK, DATA, INH	-0.3 to $V_{DD}+0.3$ V
	$V_{IN(2)}$	S44 to S47 Output OFF (Used as AD1,AD2,DSP1,DSP2)	-0.3 to $V_{DD}+0.3$ V
	$V_{IN(3)}$	OSC	-0.3 to $V_{DD}+0.3$ V
Output Voltage	V_{OUT}	OSC	-0.3 to $V_{DD}+0.3$ V
Output Current	$I_{OUT(1)}$	S1 to S53	100 uA
	$I_{OUT(2)}$	COM1,2	1.0 mA
Allowable Power Dissipation	P_{dmax}	$T_a=85^{\circ}\text{C}$	100 mW
Operating Temperature	T_{opg}		-30 to +85 °C
Storage Temperature	T_{atg}		-40 to +125 °C


Case Outline 3057 [LC7582]
(unit : mm)



Case Outline 3159 [LC7582E]
(unit : mm)



Case Outline 3190 [LC7582W]
(unit : mm)



Specifications and information herein are subject to change without notice.

SANYO Electric Co.,Ltd. Semiconductor Business Headquarters
TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN

Allowable Operating Conditions at $T_a = -30$ to $+85^\circ C$, $V_{SS} = 0V$

	Pin	min	typ	max	unit	
Supply Voltage	V_{DD}	3.0		6.5	V	
	V_{LCD}	3.0		V_{DD}	V	
Input "H"-Level Voltage	$V_{IH}(1)$	0.7 V_{DD}		6.5	V	
Input "L"-Level Voltage	$V_{IL}(1)$	0		0.3 V_{DD}	V	
Input "H"-Level Voltage	$V_{IH}(2)$	S44,S46	[Output OFF(DSP1, DSP2-used mode)]	V_{DD}	V	
Input "L"-Level Voltage	$V_{IL}(2)$	"	"	0	0.3 V_{DD}	V
Input "H"-Level Voltage	$V_{IH}(3)$	CE,CLK,DATA		0.8 V_{DD}	V	
Input "L"-Level Voltage	$V_{IL}(3)$	"	"	0	0.2 V_{DD}	V
Recommended External Resistance	R	OSC	51		kohm	
Recommended External Capacitance	C	OSC	680		pF	
OSC Guaranteed Range	f_{OSC}	OSC	25	50	kHz	
"L"-Level Clock Pulse Width	$t_{\phi L}$	CLK	0.25		usec	
"H"-Level Clock Pulse Width	$t_{\phi H}$	"	0.25		usec	
Setup Time	t_{sup}	CLK,DATA	0.25		usec	
Data Hold Time	t_{dh}	"	0.25		usec	
Serial Data Pulse Width	t_1	CE,DATA	1		usec	
"	t_2	CE,CLK	1.25		usec	
"	t_3			1	usec	
"	t_4		4		usec	




Electrical Characteristics under Allowable Operating Conditions

	Pin	min	typ	max	unit
Input "H"-Level Current	$I_{IH}(1)$ CE,CLK,DATA, $V_I = 6.5V$			5	uA
	INH				
Input "L"-Level Current	$I_{IL}(1)$ "	$V_I = 0V$		5	uA
Input "H"-Level Current	$I_{IH}(2)$ S44,S46	$V_I = V_{DD}$		10	uA
Input "L"-Level Current	$I_{IL}(2)$ "	$V_I = 0V$		10	uA
Input "H"-Level Current	$I_{IH}(3)$ AD1,AD2	$V_I = V_{DD}$		10	uA
Input "L"-Level Current	$I_{IL}(3)$ "	$V_I = 0V$		10	uA
Output "H"-Level Voltage	$V_{OH}(1)$ S1 to S53	$I_o = -10uA$	$V_{DD} - 1.0$		V
Output "L"-Level Voltage	$V_{OL}(1)$ "	$I_o = 10uA$		1.0	V
Output "H"-Level Voltage	$V_{OH}(2)$ COM1,COM2	$I_o = -100uA$	$V_{LCD} - 0.6$		V
Output "L"-Level Voltage	$V_{OL}(2)$ "	$I_o = 100uA$		0.6	V

Continued on next page.

Continued from preceding page.

		Pin		min	typ	max	unit
Center Level Voltage	V _{MID}	"	V _{LCD} =6.5V, I _O =100uA	2.65	3.25	3.85	V
"	V _{MID}	"	V _{LCD} =3.0V, I _O =100uA	0.9	1.5	2.1	V
1st Step Lighting Voltage	V _{A1}	S45,S47		0.07V _{DD}	0.1V _{DD}	0.13V _{DD}	V
2nd	"	V _{A2}	"	0.17V _{DD}	0.2V _{DD}	0.23V _{DD}	V
3rd	"	V _{A3}	"	0.27V _{DD}	0.3V _{DD}	0.33V _{DD}	V
4th	"	V _{A4}	"	0.37V _{DD}	0.4V _{DD}	0.43V _{DD}	V
5th	"	V _{A5}	"	0.47V _{DD}	0.5V _{DD}	0.53V _{DD}	V
Step Voltage Diff.	V _{step}	"	See Fig.1	0.09V _{DD}	0.1V _{DD}	0.11V _{DD}	V
OSC Frequency	f _{osc}	osc	R=51kohms, C=680pF	40	50	60	kHz
Supply Current	I _{DD}					1	mA
"	I _{DD}					2	mA
Hysteresis Voltage	V _H	V _{LCD} CE,CLK,DATA	V _{DD} =5V	0.3			V

Pin AssignmentFig.1 Step Voltage Difference
Input voltage on S45(AD2),S47(AD1)**Block Diagram**

Pin Description

- . S1 to S43 : Segment output pin
- . S46(DSP1),S44(DSP2) : Segment output or DSP input pin
- . S47(AD1),S45(AD2) : Segment output or AD input pin
- . S48(DSPOUT) : Segment output or DSP output pin
- . S49 to S53(AD01to5) : Segment output or AD output pin
- . COM1,2 : Common output pin (COM1 only is used for 1/1duty and in this case COM2 is open.)
- . V_{LCD} : LCD bias voltage setting pin
- . OSC : OSC pin
- . CE,CLK,DATA : Input pin for serial data transfer
- . V_{SS},V_{DD} : Power supply pin
- . INH : Display blanking input pin (Available for output driver only. Therefore, serial data can be also transferred during unlighting.)
- . OPEN : No connection

Data Transfer Mode

- . 1/1duty

Transfer direction (56 bits)

D1	D2	D3	D4	D5	D6	D7	D8	D47	D48	D49	D50	D51	D52	D53	D _P	D _Q	0
----	----	----	----	----	----	----	----	-------	-----	-----	-----	-----	-----	-----	-----	----------------	----------------	---

- . 1/2duty (When the number of display segments does not exceed 52, transfer data is 56 bits long. Transfer mode is the same as for 1/1 duty. Data of D54 to D106 only cannot be changed.)

Transfer direction (112 bits)

D1	D2	D3	D4	D5	D6	D7	D8	D49	D50	D51	D52	D53	D _P	D _Q	0
----	----	----	----	----	----	----	----	-------	-----	-----	-----	-----	-----	----------------	----------------	---

D54	D55	D56	D57	D58	D59	D60	D61	D62	D102	D103	D104	D105	D106	X	X	1
-----	-----	-----	-----	-----	-----	-----	-----	-----	-------	------	------	------	------	------	---	---	---

D53, D106: Dummy bit (don't care)

- D₁ to D₅₃ : Display data (1/1duty) Lighted at "1"
D₁ to D₁₀₆ : Display data (1/2duty) Unlighted at "0"

(Note) When the AD, DSP functions are selected:

- 1/1duty : D46 to D53 ----- Dummy bit (don't care)
1/2duty : D88 to D106 ----- Dummy bit (don't care)

D_P : Drive mode select bit
1/2duty at "1"
1/1duty at "0"

D_Q : AD, DSP function select bit
AD, DSP function at "1"
Segment output at "0"
X : Don't care


(Note) When the AD, DSP functions selected are not used, fix the AD1,AD2,DSP1,DSP2 pins at V_{DD} or V_{SS}.

Sample Transfers


- 1/1 duty




- 1/2 duty and 52 segments or less




- 1/2 duty and 52 segments or more




(Note) 1/2 duty and 52 segments or less do not allow transfer shown below.

**Serial Data**


- 1/1 duty (56bits)



- 1/2 duty (112bits)


**Output Waveforms**

- 1/1 duty



LC7582,7582E,7582W


. 1/2 duty



Sample Display

. Static drive (1/1duty) (AD, DSP pins are not used.)


40 segments-used application (Up to 53 segments usable)





Note: ○ : Number of segments

. 1/2duty drive

71 segments-used application (Up to 104 segments usable)



Sample Application Circuit 1**Sample Application Circuit 2**

Note) The internal display data is indeterminate immediately after V_{DD} rise. If the display is kept lighted as it is, the display will have no meaning. The display is forced to be unlighted when the INH is at "L" level. Do not release ("H") until the transfer of display data from the controller is completed.

Correspondence between Transfer (External Input) Data and Output Pin

(Note) COM1 only is used at 1/1 duty.

Output pin	0		1		COM1	COM2
	DQ	0	1	0	1	
	1/1 duty		1/2 duty			
S1	D1	D1	D1	D1	O	
			D2	D2		O
S2	D2	D2	D3	D3	O	
			D4	D4		O
S3	D3	D3	D5	D5	O	
			D6	D6		O
S26	D26	D26	D51	D51	O	
			D52	D52		O
S27	D27	D27	D54	D54	O	
			D55	D55		O
S28	D28	D28	D56	D56	O	
			D57	D57		O
S43	D43	D43	D86	D86	O	
			D87	D87		O
S44	D44	D44	D88	DSP 2	O	
			D89			O
S45	D45	D45	D90	ALI	O	
			D91			O
S46	D46	DSP 1	D92	DSP 1	O	
			D93			O
S47	D47	ARI	D94	ARI	O	
			D95			O
S48	D48	DISPO1	D96	DSPO1	O	
			D97			O
S49	D49	ARO1	D98	ARO1	O	
			D99			O
S50	D50	ARO2	D100	ARO2	O	
			D101			O
S51	D51	ARO3	D102	ARO3	O	
			D103			O
S52	D52	ARO4	D104	ARO4	O	
			D105			O
S53	D53	ARO5	Always lighting	ARO5	O	
			Always lighting			O

Note

- DSP1 : External display input data name. The output is DSPO1.
- DSPO1 : External display output data name. The input is DSP1.
- DSP2 : External display input data name. The output is DSPO2.
- DSPO2 : External display output data name. The input is DSP2.
- ARI : AD converter input data name. The output is ARO1 to 5.
- ARO1 to 5 : AD converter output data name. The input is ARI.
- ALI : AD converter input data name. The output is AL01 to 5.
- AL01 to 5 : AD converter output data name. The input is ALI.

OSC Frequency

When determining the OSC frequency, see below.

Fig. 1 OSC Frequency at OSC Pin vs. CR





Fig. 2 OSC Frequency at OSC Pin vs. V_{DD}



Recommended external resistor value 10kohms to 100kohms (carbon)

Recommended external capacitor value 330pF to 3300pF

330pF to 820pF (ceramic, temperature coefficient: 0)

1000pF to 3300pF (polyester, temperature coefficient: plus)

Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringement of intellectual property rights or other rights of third parties.