

Product Specification:

Model		UPS-2200D
Power		2200VA/1300W
Technology		Line Interactive
Input	Input Voltage Range	145-275Vac/90Vac-140Vac±3%
	Nominal Input Voltage	220/230/240/110/120Vac
	Input Frequency	50/60Hz
Output	Max Input Current	8.4A/16.8A
	Nominal Output Voltage	220/230/240/110/120Vac
	Max Output Current	5.9A/11.8A
	Output Voltage Range(Normal Mode)	220/230/240/110/120Vac+10%~15%
	Output Voltage Range(Battery Mode)	220/230/240/110/120Vac±10%
	Output Frequency(Normal Mode)	Synchronized(Sine Wave)
	Output Frequency(Battery Mode)	50/60Hz
	Wave Form	Step Wave
	Power Factor	0.6
Efficiency		> 90%
Transfer Time		< 10ms
Batteries&Runtime	Battery Type	Maintenance-free Sealed Lead-Acid Battery,Leakproof
	Included Battery Modules	4×12V/7.0Ah
	Runtime	Full Load 4 Minutes Half Load 12 Minutes
	Charge Time	<5 Hours(90%)
LCD Status Display		Output Voltage,Normal,Fault,Battery,Overload,Battery Level
Audible Alarm	Buzzer	AC Unusual/Battery Low Voltage/Overload/Short Circuit/PCB Failed,Beep for 240 Seconds
Interface Port(s)	Interface	RS-232/USB optional
	Control Software	UPSilon2000
Cold-start Capability		Yes
Protection	Surge Protection and Filtering	High Voltage,Low Voltage,Surge,Spike
	Overload Protection	120%~150%
	Battery Low Voltage Protection	40V
	Output Short Circuit Protection	Output auto cut off,Buzzer beeping
	EMI Filter	Yes
	Tel/Fax/Modem Jack	Yes
Regulatory Approvals		CE
Operating Conditions	Operating Temperature	0-40°C
	Storage Temperature	-15-45°C
	Operating Relative Humidity	10%RH-95%RH,Non-condensing
Dimension	Inner Box(mm)	593*220*305
	Unit Weight(kgs)	25