



- 1. MATERIAL :**
 1-1. HOUSING : PBT UL94V-0 ; COLOR : BLACK.
 1-2. CONTACT : BRASS.
 1-3. SHELL A : BRASS.
 1-4. SHELL B : BRASS.
 1-5. POM RING : POM ; COLOR : BLACK.
 1-6. SPRING : STAINLESS STEEL.
 1-7. PLASIC TUBE : ABS ; COLOR : BLACK.
 1-8. METAL CAP : PVC ; COLOR : BLACK.
 1-9. PLASTIC COVER : ABS ; COLOR : BLACK.
 1-10.CLAMP : BRASS
- 2. FINISH :**
 2-1. CONTACT : 50 MICRO INCHES MIN. SILVER PLATED
 2-2. SHELL A : NICKEL PLATED 60u" ~ 100u" OVER ALL.
 2-3. SHELL B : NICKEL PLATED 60u" ~ 100u" OVER ALL.
 2-4. SPRING : NICKEL PLATED 60u" ~ 100u" OVER ALL.
 2-5. CLAMP : BRIGHT TIN 60u" ~ 100u" OVER ALL.
- 3. ELETRICAL SPECIFICATION :**
 3-1. RATED CURRENT : 7.5A/DC MAX
 3-2. VOLTAGE : 25V/DC MAX
- 4. ENVIRONMENTAL :**
 4-1. OPERATION TEMPERATURE : -20 ℃~85℃.

7.0
6.5
5.5
5.0
4.0
SR OD

RoHS Compliant			
APPD. 核准 HELEN	SCALE 比例 參考	TOLERANCE 容許公差	PART NAME 品名 POWER DIN 3PIN PLUG ASSEMBLY TYPE SINGLE-ARROW SR OD:6.5mm SILVER PLATING BLACK COLORROHS
DWG. 製圖 ABBY		UNIT 單位 MM	
DATE 制表日 2019/11/06	PAGE 張數 1 OF 1	REV. 版次 A	PART NO. 料號 PC-MDP-401-3P