



RSWG

– Heat Shrinkable Braided Sleeve

Heat shrinkable braided sleeve is made of PET and polyolefin filament. It will shrink after heating. The unique braided structure makes the product very soft and easy to install even on hoses and special-shaped parts. Excellent wear resistance and noise reduction.



Features

- Shrink ratio: 2:1
- Initial shrink temperature: $\geq +80^{\circ}\text{C}$
- Fully shrink temperature: $\geq +120^{\circ}\text{C}$
- Operating temperature: $-40^{\circ}\text{C}\sim +125^{\circ}\text{C}$
- Flame retardant grade: self-extinguishing within 60s
- Environmental standard: RoHS
- Standard color: black

Dimensions

Size	As Supplied		After Recovery	Package (m/roll)
	Fold diameter	Inner Diameter(mm)	Inner Diameter (mm)	
Φ6.0/3.0	14±3	≥ 6.0	≤ 3.0	100
Φ10.0/5.0	18±3	≥ 10.0	≤ 6.0	100
Φ12.0/6.0	24±3	≥ 12.0	≤ 6.0	100
Φ16.0/8.0	29±3	≥ 16.0	≤ 8.0	100
Φ20.0/10.0	36±3	≥ 20.0	≤ 10.0	100
Φ25.0/12.5	44±3	≥ 25.0	≤ 12.5	100
Φ30.0/15.0	53±4	≥ 30.0	≤ 15.0	50
Φ35.0/17.5	60±4	≥ 35.0	≤ 17.5	50
Φ40.0/20.0	68±4	≥ 40.0	≤ 20.0	50
Φ50.0/25.0	85±5	≥ 50.0	≤ 25.0	50
Φ60.0/30.0	100±5	≥ 60.0	≤ 30.0	50
Φ70.0/35.0	116±5	≥ 70.0	≤ 35.0	50
Φ80.0/40.0	132±5	≥ 80.0	≤ 40.0	50
Φ90.0/45.0	148±5	≥ 90.0	≤ 45.0	50

