



SCHOTTKY BARRIER RECTIFIER

SR3020P THRU SR30100P

VOLTAGE RANGE

20 to 100 Volts

CURRENT


30.0 Amperes

FEATURES

- Plastic package has Underwriters Laboratory Flammability classification 94V-O utilizing Flame Retardant Epoxy Molding Compound
- Exceeds environmental standards of MIL-S-19500/228
- Low power loss, high efficiency
- Low forward voltage, high current capability
- High surge capacity
- For use in low voltage, high frequency inverters. Free wheeling, and polarity protection applications

MECHANICAL DATA

- Case: TO-3P molded Plastic
- Terminals: Lead solderable per MIL-STD-202, Method 208
- Polarity: as marked
- Mounting position: Any
- Weight: 0.2ounce, 5.6 grams



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

		SYMBOLS	SR 3020P	SR 3030P	SR 3035P	SR 3040P	SR 3045P	SR 3050P	SR 3060P	SR 3080P	SR30 100P	SR30 150P	SR30 200P	UNIT
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	20	30	35	40	45	50	60	80	100	150	200	Volts
Maximum RMS Voltage		V _{RMS}	14	21	25	28	32	35	42	56	70	105	140	Volts
Maximum DC Blocking Voltage		V _{DC}	20	30	35	40	45	50	60	80	100	150	200	Volts
Maximum Average Forward Rectified Current At T _C =110°C		I _(AV)	30.0											Amps
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)		I _{FSM}	250											Amps
Maximum Forward Voltage at 15.0A per element		V _F	0.65			0.72			0.75			0.85		Volts
Maximum DC Reverse Current at rated DC Blocking Voltage per element	T _C = 25°C	I _R	1.0											mA
	T _C = 100°C		100											
Typical Junction Capacitance Range		C _J	500											pF
Typical Thermal Resistance (Note 1)		R _{θJC}	1.2											°C/W
Operating Storage Temperature Range		T _J T _{STG}	(-55 to +150)											°C

Notes:

- Thermal Resistance Junction to Ambient
- Measured at $V_R=4\text{V}$ and $f=1\text{MHz}$



SCHOTTKY BARRIER RECTIFIER

SR3020P THRU SR30100P

VOLTAGE RANGE 20 to 100 Volts
CURRENT 30.0 Ampere

RATINGS AND CHARACTERISTIC CURVES SRF1620 THRU SRF16100

FIG.1-FORWARD CURRENT
DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE
SURGE CURRENT




FIG.3-TYPICAL REVERSE
CHARACTERISTICS




FIG.4-TYPICAL FORWARD
CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

